

PRODUCTS

AC/DC Digital Clamp Meters

- Multimeters
- Voltage Testers
- Clamp Meters
- Loggers
- Insulation Testers
- Earth Testers
- LOOP/PFC/PSC Testers
- RCD Testers
- Multi Function Testers
- Portable Appliance Testers
- Power Meters
- Sensors, Multi-Trans, Clamp Adaptors
- Others
- Accessories
- Discontinued Products

KEW

2056R

[Selection Guide](#) [Product Catalogue](#) [Instruction Manual](#)

- Designed to meet international safety standard IEC 61010-1 CAT IV 600V.
- CAT IV Clamp Meters can measure the Voltage and Current in both very low and high power circuits.
- Thus, very useful for power distribution companies, power utilities and maintenance fields.
- True RMS enables an accurate measurement.



TRUE RMS	CAT IV 600V		
Φ40	MAX AC/DC1000A	AC V	DC V
Hz	Ω	Continuity	°C



AC A	0 - 600.0/1000A ±2.0%rdg±5dgt (50/60Hz) ±3.5%rdg±5dgt (40 - 500Hz)
DC A	0 - 600.0/1000A ±1.5%rdg±5dgt
AC V	6/60/600V Auto Ranging ±1.5%rdg±4dgt (50/60Hz) ±3.5%rdg±5dgt (40 - 400Hz)
DC V	600m/6/60/600V Auto Ranging ±1.0%rdg±3dgt
Ω	600/6k/60k/600k/6M/60MΩ (Auto Ranging) ±1%rdg±5dgt (600 - 6M) / ±5%rdg±8dgt (60M)
Continuity buzzer	Buzzer Sounds at 100Ω
Frequency/DUTY	10/100/1k/10kHz (Auto Ranging) / 0.1 - 99.9%
Temperature	-50°C - +300°C (With the use of Temperature probe 8216)
Conductor Size	Ø40mm
Withstand Voltage	6880V AC for 5 seconds
Safety Standard	IEC 61010-1 CAT IV 600V, IEC 61010-031, IEC 61010-2-032, IEC 61326
Power Source	R03 (1.5V) (AAA) × 2
Dimensions	254(L) × 82(W) × 36(D)mm
Weight	310g
Accessories	7066A (Test leads) 9094 (Carrying case) Instruction Manual
Optional	8008 (Multi-Tran) 8216 (Temperature probe)